


Precision Display Socket 2,54 mm

Series

218

Product group
1




Rated current	3,0 A
Rated voltage	150 VRMS / VDC
Withstand voltage	1000 VRMS for one minute
Material contact	Copper alloy
Material clip	BeCu
Material insulator	High temp. thermoplast UL94V-0
Operating temperature	-55°C to +125°C
Max. soldering temper.	260°C for 10 seconds

pitch	2,54
termination	
mating pin size	ø 0,40-0,56 □ 0,25x0,45
max. pincount	040

All dimensions in mm.


Variation



1

no. of contacts	row distance (code)	row distance (mm)	see figure left	see figure left	see figure left
n		D	A	B	C
006	3	7,62	7,54	10,08	7,62
008	3	7,62	10,08	10,08	7,62
010	2	5,08	12,62	7,60	5,08
010	3	7,62	12,62	10,08	7,62
014	3	7,62	17,70	10,08	7,62
016	3	7,62	20,24	10,08	7,62
018	3	7,62	22,78	10,08	7,62
020	3	7,62	25,32	10,08	7,62
024	3	7,62	30,40	10,08	7,62
024	6	15,24	30,40	17,70	7,62
028	6	15,24	35,48	17,70	7,62
032	6	15,24	40,56	17,70	7,62
040	6	15,24	50,72	17,70	7,62

Clip style: S = 4 finger clip
 Plating: T = Sn, F = Au, H = Au 0,75 μ
 Packaging: T = Tube



www.mpe-connector.de

Order code:

218-1- - -X0ST -XT0

MPE-Garry GmbH • Schäfflerstraße 13 • 87629 Füssen • Germany • Phone: +49 (0) 83 62 / 91 56-0 • Fax: +49 (0) 83 62 / 91 56-500 • Email: vk@mpe-connector.de • www.mpe-connector.de